

# Change Notice

# JW Series

## Change to JWL & JWLW Rockers' Contact Material

Type of Change:

- Engineering     Part Number
- Product         Appearance

JWL and JWLW rockers will have a revision to the stationary contact material. The material will change from silver alloy with silver plating to silver alloy plus copper with silver plating. This change will effect all single and double pole models, both standard and custom. The following table describes the difference before and after the modification.



JWL Rocker

Stationary Contacts Before Change	Stationary Contacts After Change																																																
Silver Alloy with Silver Plating	Silver Alloy plus Copper with Silver Plating																																																
<div style="text-align: center; margin-bottom: 10px;"> <span style="border: 1px solid black; padding: 2px 10px; font-weight: bold;">JW</span> <span style="border: 1px solid black; padding: 2px 10px; font-weight: bold;">LW</span> <span style="border: 1px solid black; padding: 2px 10px; font-weight: bold;">2</span> <span style="border: 1px solid black; padding: 2px 10px; font-weight: bold;">1</span> <span style="border: 1px solid black; padding: 2px 10px; font-weight: bold;">R</span> <span style="border: 1px solid black; padding: 2px 10px; font-weight: bold;">A</span> <span style="border: 1px solid black; padding: 2px 10px; font-weight: bold;">1</span> <span style="border: 1px solid black; padding: 2px 10px; font-weight: bold;">A</span> <span style="border: 1px solid black; padding: 2px 10px; font-weight: bold;">—</span> <span style="border: 1px solid black; padding: 2px 10px; font-weight: bold;"> </span> </div> <table border="1" style="width: 100%; border-collapse: collapse; margin-bottom: 10px;"> <thead> <tr> <th colspan="2" style="background-color: #cccccc;">Ratings</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">L</td> <td>16A @ 125/250V AC</td> </tr> <tr> <td style="text-align: center;">LW</td> <td>Panel Seal 16A @ 125/250V AC</td> </tr> </tbody> </table> <table border="1" style="width: 100%; border-collapse: collapse; margin-bottom: 10px;"> <thead> <tr> <th colspan="2" style="background-color: #cccccc;">Poles</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td>SPST SPDT</td> </tr> <tr> <td style="text-align: center;">2</td> <td>DPST DPDT</td> </tr> </tbody> </table> <p style="font-size: small;">Notes: DPST must have international ON-OFF symbols for VDE approval. JWLW available in DPST &amp; DPDT only.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="4" style="background-color: #cccccc;">Circuits</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">ON</td> <td style="text-align: center;">NONE</td> <td style="text-align: center;">OFF</td> </tr> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">ON</td> <td style="text-align: center;">NONE</td> <td style="text-align: center;">ON</td> </tr> </tbody> </table>	Ratings		L	16A @ 125/250V AC	LW	Panel Seal 16A @ 125/250V AC	Poles		1	SPST SPDT	2	DPST DPDT	Circuits				1	ON	NONE	OFF	2	ON	NONE	ON	<table border="1" style="width: 100%; border-collapse: collapse; margin-bottom: 10px;"> <thead> <tr> <th colspan="2" style="background-color: #cccccc;">Barrier Types</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">R</td> <td>No Barrier</td> </tr> <tr> <td style="text-align: center;">B</td> <td>With Barrier</td> </tr> </tbody> </table> <p style="font-size: small;">Note: JWLW combines with code R only.</p> <table border="1" style="width: 100%; border-collapse: collapse; margin-bottom: 10px;"> <thead> <tr> <th colspan="2" style="background-color: #cccccc;">Cap Colors</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">A</td> <td>Black</td> </tr> <tr> <td style="text-align: center;">B</td> <td>Ivory</td> </tr> <tr> <td style="text-align: center;">C</td> <td>Red</td> </tr> <tr> <td style="text-align: center;">H</td> <td>Gray</td> </tr> </tbody> </table> <p style="font-size: small;">Note: JWLW available with black or red caps only.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="background-color: #cccccc;">Inscription Orientation</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">No Code</td> <td>No Inscription</td> </tr> <tr> <td style="text-align: center;">1</td> <td>Horizontal</td> </tr> <tr> <td style="text-align: center;">2</td> <td>Vertical</td> </tr> </tbody> </table> <p style="font-size: small;">These are inscriptions for Single Throw models only.</p>	Barrier Types		R	No Barrier	B	With Barrier	Cap Colors		A	Black	B	Ivory	C	Red	H	Gray	Inscription Orientation		No Code	No Inscription	1	Horizontal	2	Vertical
Ratings																																																	
L	16A @ 125/250V AC																																																
LW	Panel Seal 16A @ 125/250V AC																																																
Poles																																																	
1	SPST SPDT																																																
2	DPST DPDT																																																
Circuits																																																	
1	ON	NONE	OFF																																														
2	ON	NONE	ON																																														
Barrier Types																																																	
R	No Barrier																																																
B	With Barrier																																																
Cap Colors																																																	
A	Black																																																
B	Ivory																																																
C	Red																																																
H	Gray																																																
Inscription Orientation																																																	
No Code	No Inscription																																																
1	Horizontal																																																
2	Vertical																																																
<table border="1" style="width: 100%; border-collapse: collapse; margin-bottom: 10px;"> <thead> <tr> <th colspan="2" style="background-color: #cccccc;">Housing Colors</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">A</td> <td>Black</td> </tr> <tr> <td style="text-align: center;">B</td> <td>Ivory</td> </tr> <tr> <td style="text-align: center;">H</td> <td>Gray</td> </tr> </tbody> </table> <p style="font-size: small;">Note: JWLW available with black only.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="background-color: #cccccc;">Barrier Colors</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">A</td> <td>Black</td> </tr> <tr> <td style="text-align: center;">B</td> <td>Ivory</td> </tr> <tr> <td style="text-align: center;">H</td> <td>Gray</td> </tr> </tbody> </table>		Housing Colors		A	Black	B	Ivory	H	Gray	Barrier Colors		A	Black	B	Ivory	H	Gray																																
Housing Colors																																																	
A	Black																																																
B	Ivory																																																
H	Gray																																																
Barrier Colors																																																	
A	Black																																																
B	Ivory																																																
H	Gray																																																

The target part numbers effected by this Change Notice include all combinations of JWL and JWLW.

**Notes**

There are no changes to the movable contacts.  
 There are no changes to specifications, ratings or electrical life.  
 Contact factory if more details are needed.

**Effective Date**

Changes to JWL and JWLW stationary contact material will be effective November 2015.



<http://www.nkkswitches.com> • 1.877.2BUYNKK (228.9655)

7850 East Gelding Drive • Scottsdale, AZ 85260 • Telephone 480.991.0942 • Fax 480.998.1435