

ROCKERS

MAXIMUM RATING	SIZE	MOUNTING				TERMINALS					PROCESS SEAL	SERIES
		PC Board	Bush-ing	Snap-in	Two Screw	Solder Lug	PC	Quick Connect	Wire-Wrap	Screw		
0.4VA @ 28V AC/DC	ultra-mini	•					•				•	G
0.4VA @ 28V AC/DC	ultra-mini	•					•					GW
0.4VA @ 28V AC/DC	submini	•					•				•	A
0.4VA @ 28V AC/DC	miniature	•		•	•	•	•	•	•			M
0.4VA @ 28V AC/DC	miniature	•					•				•	M2T
3A @ 250V AC	miniature			•		•						CWT
6A @ 125V AC	miniature			•		•						CWT
6A @ 125V AC	miniature	•		•	•	•	•	•	•			M
6A @ 125V AC	miniature	•					•				•	M2T
6A @ 250V AC	miniature	•		•		•	•	•				CWS
10A @ 125V AC	standard				•	•	•	•				P
10A @ 125/250V AC	miniature			•		•		•				JWS
10A @ 125/250V AC	standard			•		•		•				JWM
15A @ 125/250V AC	standard			•		•		•	Wire Lead	•		WR
16A @ 125/250V AC	standard			•		•		•				JWL
15~20A @ 125V AC	standard				•	•						SW Med
30A @ 125V AC/DC	standard				•					•		SW Hi Cap