

## PUSHBUTTONS

MAXIMUM RATING	SIZE	MOUNTING				TERMINALS					PROCESS SEAL	SERIES
		PC Board	Bush-ing	Snap-in	Two Screw	Solder Lug	PC	Quick Connect	Wire-Wrap	Screw		
0.4VA @ 28V AC/DC	ultra-mini	•					•				•	GB
0.4VA @ 28V AC/DC	ultra-mini	•					•					GB2
0.4VA @ 28V AC/DC	submini	•					•				•	AB
0.4VA @ 28V AC/DC	submini	•					•				•	BB
0.4VA @ 28V AC/DC	miniature	•	•	•		•	•					EB
0.4VA @ 28V AC/DC	submini		•				Turret					FB
0.4VA @ 28V AC/DC	miniature	•	•	•		•	•					KB
0.4VA @ 28V AC/DC	miniature	•					•				•	M2B
0.4VA @ 28V AC/DC	miniature	•	•	•		•	•	•	•			MB2000
0.4VA @ 28V AC/DC	miniature	•	•	•		•	•		•			MB2400
0.4VA @ 28V AC/DC	miniature	•		•		•	•					UB
0.4VA @ 28V AC/DC	miniature	•		•		•	•					UB2
0.4VA @ 28V AC/DC	miniature		•	•		•	•	•				YB
0.4VA @ 28V AC/DC	miniature		•			•						SB4011
0.4VA @ 28V AC/DC	standard	•	•	•		•	•	•				LB
0.1A @ 30V AC/DC	submini		•			•						HB
500mA @ 125V AC	submini		•				Turret					FB
1A @ 125V AC	miniature	•					•				•	M2B
1A @ 125/250V AC	miniature	•	•	•		•	•					KB
3A @ 125V AC	miniature	•	•	•		•	•					EB
3A @ 125V AC	miniature	•	•	•		•	•		•			MB2400
3A @ 125V AC	miniature		•			•						SB4011
3A @ 125/250V AC	miniature		•	•		•		•				LP01
3A @ 125/250V AC	miniature		•	•		•	•	•				YB
3A @ 125/250V AC	standard	•	•	•		•	•	•				LB
5A @ 125/250V AC	miniature	•		•		•	•					UB
5A @ 125/250V AC	miniature	•		•		•	•					UB2
6A @ 125V AC	miniature	•	•	•		•	•	•	•			MB2000
6A @ 125V AC	standard		•			•		Wire Lead		•		WB
10A @ 125/250V AC	standard			•		•		•				JPM
15A @ 125V AC	standard		•			•				•		SB
15A @ 125V AC	standard		•					•				SCB
16A @ 125/250V AC	standard			•		•		•				JPL