

TOGGLES

MAXIMUM RATING	SIZE	MOUNTING				TERMINALS						PROCESS SEAL	SERIES
		PC Board	Bush-ing	Snap-in	Two Screw	Solder Lug	PC	Quick Connect	Wire-Wrap	Screw	SMD Gull Wing		
0.4VA @ 28V AC/DC	ultra-mini	•					•					•	G
0.4VA @ 28V AC/DC	ultra-mini										•	•	G3T
0.4VA @ 28V AC/DC	submini	•					•					•	A
0.4VA @ 28V AC/DC	submini	•					•					•	B
0.4VA @ 28V AC/DC	miniature	•	•			•	•	•	•				M
0.4VA @ 28V AC/DC	miniature	•					•					•	M2T
0.4VA @ 48V AC/DC	miniature	•	•				•						D2
6A @ 125V AC	miniature	•	•			•	•	•	•				M
6A @ 125V AC	miniature	•					•					•	M2T
10A @ 125V AC	standard	•	•			•	•	•					P
10A @ 125V AC	standard		•			•			Wire Lead	•			WT
5A @ 125V AC	standard		•			•							S Low Cap
15~20A @ 125V AC	standard		•			•		•					S Med Cap
15~25A @ 125V AC	standard		•			•		•		•			S Med/Hi
30~50A @ 125V AC	standard		•							•			S Hi Cap
30A @ 125V AC/DC	standard		•							•			S AC/DC