


Change Notice

UB Series

Super Bright LED Specifications



Type of Change:




- Engineering Part Number
 Product Appearance

The specifications for Super Bright LEDs has changed. This change does not affect Bright LEDs.

This change will affect the following products:

All **UB Series** (switches and indicators) Super Bright LED models.

UB2 Series products are not affected.

Super Bright LEDs are Electrostatic Sensitive	 	Before Change			After Change			Unit
		6B	6F	6G	6B	6F	6G	
(+) —  — (-)	Color	Red	Amber	Green	White	Green	Blue	
Forward Peak Current	I_{FM}	25	25	25	30	30	30	mA
Continuous Forward Current	I_F	20	20	20	20	20	20	mA
Forward Voltage	V_F	3.8	3.8	3.8	3.2	3.2	3.2	V
Reverse Peak Voltage	V_{RM}	5	5	5	5	5	5	V
Current Reduction Rate Above 25°C	ΔI_F	0.47	0.47	0.47	0.40	0.40	.040	mA/°C
Ambient Temperature Range		-25° ~ +50°C			-25° ~ +50°C			

Effective Date

Change will be effective immediately.

NKK
SWITCHES

www.nkkswitches.com
1.877.2BUYNKK (228.9655)

7850 East Gelding Drive • Scottsdale, AZ 85260
Telephone 480.991.0942 • Fax 480.998.1435