Change Notice

Changes for LCD Driver in SmartSwitch 36 x 24 Switches & Displays

Type of	Change:
---------	---------

✓ Engineering✓ Part Number✓ Product✓ Appearance

This change is a product improvement by a redesign of the LCD driver to accommodate low voltage logic and control. The revision should be transparent to the current applications and allow for lower voltage design and higher frequency for future applications.

The changes will effect all IS Series 36×24 switches and displays, both standard and custom. The specification differences are outlined below, followed by effected standard part numbers.



LCD Driver Changes for Switches & Displays

Item	Symbol	Before Change	After Change
Supply Voltage for Logics	V _{DD}	4.5V to 5.5V	3.0V to 5.5V
Clock Operation Frequency	f _{SCP}	6.0MHz Maximum	8.0MHz Maximum
Clock High Level Pulse Width	t _{CWH}	70ns	50ns
Clock Low Level Pulse Width	t _{CWL}	70ns Minimum	50ns Minimum
Latch High Level Width	t _{LWH}	200ns Minimum	50ns Minimum

IS Series Sta	IS Series Standard Part Numbers Effected by LCD Driver Change			
Wide View LCD	Wide View LCD Compact	Wide View Display		
IS15BBFP4RGB	IS15BSBFP4RGB	IS01BBFRGB		
IS15BAFP4CF	ISBSBFP4EF	IS01BBFEF		
	IS15BSAFP4CF			

Notes

- There are no changes to external dimensions or specifications other than what is shown above.
- · Contact the factory if further details are needed.

Effective Date

Changes to IS Series 36 x 24 Switches & Displays will be effective February 2017.



http://www.nkkswitches.com • 1.877.2BUYNKK (228.9655)

7850 East Gelding Drive • Scottsdale, AZ 85260 • Telephone 480.991.0942 • Fax 480.998.1435