Change Notice

M Series Toggles

Change of Red/Green Bicolor LED Specification

Type of Change:

☑ Engineering☑ Part Number☑ Product☑ Appearance

The LED specifications for M2100 toggle & rocker switches (not paddles) with red/green bicolor LED will change.

This change will affect all M2100 toggle & rocker switches with red/green bicolor LED including all custom products.

Bicolor LED Specifications						
			From Curren	t Bicolor LED	To New Bicolor LED	
LEDs are an integral part of the switch and are not available separately. Bicolor is white in OFF state.			F	C	F	C
		Color	Green	Red	Green	Red
	Forward Peak Current	I _{FM}	25mA	25mA	25mA	25mA
	Continuous Forward Current	l _F	10mA	10mA	10mA	10mA
	Forward Voltage	$V_{\scriptscriptstyle F}$	1.9V	1.9V	2.0V	1.7V
	Current Reduction Rate Above 25°C	Δ_{IF}	0.33 mA/°C	0.33 mA/°C	0.33 mA/°C	0.33 mA/°C
	Ambient Temperature Range	Ta	−10°C ~ +55°C		−10°C ~ +55°C	

- · No change to dimensions.
- · Forward Voltage will be changed. Please make sure to use appropriate resistor.
- · Contact factory for further details.

Effective Date

Change will be effective with December 2011 production.



www.nkkswitches.com 1.877.2BUYNKK (228.9655) 7850 East Gelding Drive • Scottsdale, AZ 85260 Telephone 480.991.0942 • Fax 480.998.1435